

PERFORMANCE SPECIFICATION

CAPACITORS, FIXED, ELECTROLYTIC (SOLID ELECTROLYTE), TANTALUM
ESTABLISHED RELIABILITY, GENERAL SPECIFICATION FOR

This supplement forms a part of MIL-PRF-390003J, dated 18 November 2002

SPECIFICATION SHEETS

MIL-PRF-39003/1	Capacitors, Fixed, Electrolytic (Solid Electrolyte), Tantalum, (Polarized, Sintered Slug), Established Reliability, Style CSR13.
MIL-PRF-39003/2	Capacitors, Fixed, Electrolytic (Solid Electrolyte), Tantalum, (Polarized, Sintered Slug), Established Reliability, Style CSR09.
MIL-PRF-39003/3	Capacitors, Fixed, Electrolytic (Solid Electrolyte), Tantalum, (Polarized, Sintered Slug), Established Reliability, Style CSR23.
MIL-PRF-39003/4	Capacitors, Fixed, Electrolytic (Solid Electrolyte), Tantalum, (Nonpolarized, Sintered Slug), Established Reliability, Style CSR91.
MIL-PRF-39003/6	Capacitors, Fixed, Electrolytic (Solid Electrolyte), Tantalum, (Polarized, Sintered Slug), Established Reliability, Style CSR33.
MIL-PRF-39003/9	Capacitors, Fixed, Electrolytic (Solid Electrolyte), Tantalum, (Polarized, Sintered Slug), Established Reliability, Style CSR21.
MIL-PRF-39003/10	Capacitors, Fixed, Electrolytic (Solid Electrolyte), Tantalum, (Polarized, Sintered Slug), Established Reliability, Styles CSS13 and CSS33 (High Reliability Applications).

Custodians:
Army – CR
Navy - EC
Air Force – 11

Preparing activity:
DLA - CC
(Project 5910-2236)

Review activities:
Navy – AS, MC, OS, SH
Air Force – 19, 99

AMSC N/A
DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

FSC 5910